

w w w . w e l l p r o . c o m

PIPE COUPLINGS/INSERT FITTINGS FOR PUMPS

STAINLESS STEEL, BRASS & PVC PIPE COUPLINGS/FITTINGS



*The Water Well
Products
used by
PROFESSIONALS*



"The Best Selection, Quality, and Price"

Drop Pipe Couplings

For threaded pipe to submersible pump or other threaded pipe coupling needs

Chamfered ends for quick, easy starting of threads. Tapered pipe threads for positive, watertight connection.



Galvanized Merchant Coupling



PVC Drop Pipe Coupling



Brass Drop Pipe Coupling



Stainless Steel Drop Pipe Coupling



PVC Meter Coupling



Stainless Steel Drop Pipe Coupling



Drive Coupling



Male Adapter



Extra Long Male Adapter



Rope Adapter



Stainless Steel Male Adapter



Stainless Steel Extra Long Male Adapter

Order No.	UPC Bar Code (Qty. 1)	Pipe Size	Length Inches	Material	Ctn. Qty.	Approx. Wt./Lbs.
WGDC100	6 42367 08353 3	1"	2"	Galv. Merchant	1	0.4
WGDC125	6 42367 08354 0	1-1/4"	2-1/16"	Galv. Merchant	1	0.5
WPDC100	6 42367 08355 7	1"	2-3/4"	PVC Heavy Sch. 80	1	0.1
WPDC125	6 42367 08356 4	1-1/4"	2-3/4"	PVC Heavy Sch. 80	1	0.2
WPDCH100	6 42367 08357 1	1"	2-3/4"	PVC Extra Heavy Sch. 120	1	0.2
WPDCH125	6 42367 08358 8	1-1/4"	2-3/4"	PVC Extra Heavy Sch. 120	1	0.2
WPDCH150	6 42367 08359 5	1-1/2"	3-3/16"	PVC Extra Heavy Sch. 120	1	0.2
WPDCH200	6 42367 08360 1	2"	3-3/16"	PVC Extra Heavy Sch. 120	1	0.3
WBDC100	6 42367 08361 8	1"	2-3/8"	Brass	1	0.7
WBDC125	6 42367 08362 5	1-1/4"	2-3/8"	Brass	1	0.8
WBDC200	6 42367 10457 3	2"	2-1/2"	Brass	1	1.1
WSSDC100	6 42367 10448 1	1"	2-1/2"	Stainless Steel	1	0.7
WSSDC125	6 42367 10449 8	1-1/4"	2-1/2"	Stainless Steel	1	0.9
WSSMC150	6 42367 10455 9	1-1/2"	2"	Stainless Steel	1	0.8
WSSMC200	6 42367 10456 6	2"	2-1/4"	Stainless Steel	1	1.1

PVC Meter Coupling

For FIP x SLIP (glue end)

Chamfered ends for quick, easy starting of threads. Tapered pipe threads for positive, watertight connection. One end has deep socket for an easy glued connection.

Order No.	UPC Bar Code (Qty. 1)	Pipe Size	Length Inches	Material	Ctn. Qty.	Approx. Wt./Lbs.
WPMCH100	6 42367 08363 2	1"	3-7/16"	PVC Extra Heavy Sch. 120	1	0.2

Drive Couplings - For threaded pipe to drive well points

Recessed threads. Heavy duty wall.

Order No.	UPC Bar Code (Qty. 1)	Pipe Size	Length Inches	Material	Ctn. Qty.	Approx. Wt./Lbs.
WDRCOUP125	6 42367 08364 9	1-1/4"	2-3/4"	Galvanized Steel	1	0.9
WDRCOUP200	6 42367 08365 6	2"	3-3/8"	Galvanized Steel	1	1.8

Red Brass Male & Rope Adapters - For coiled plastic pipe to submersible pump

Order No.	UPC Bar Code (Qty. 1)	MIP Insert Size x Size	Length Inches	Ctn. Qty.	Approx. Wt./Lbs.
Male Adapters					
WRBMA100 (Round)	6 42367 08366 3	1" x 1"	2.8"	1	0.3
WRBMA100 (Hex)	6 42367 07864 5	1" x 1"	3.5"	1	0.5
* WRBMA100XL (Hex)	6 42367 08367 0	1" x 1"	4.5"	1	0.5
WRBMA1025 (Hex)	6 42367 08368 7	1-1/4" x 1"	3.5"	1	0.5
* WRBMA1025XL (Hex)	6 42367 08369 4	1" x 1-1/4"	4.5"	1	0.6
WRBMA125 (Hex)	6 42367 07865 2	1-1/4" x 1-1/4"	3.25"	1	0.6
* WRBMA125XL (Hex)	6 42367 08370 0	1-1/4" x 1-1/4"	4.5"	1	0.7
* WRBMA200XL (Hex)	6 42367 08516 2	2" x 2"	4.3"	1	1.3
Rope Adapters (Includes eyelet for safety rope)					
WRBLA100 (Round)	6 42367 07870 6	1" x 1"	4.0"	1	0.5
WRBLA2510 (Round)	6 42367 08371 7	1-1/4" x 1"	4.0"	1	0.6
WRBLA125 (Round)	6 42367 08372 4	1-1/4" x 1-1/4"	4.0"	1	0.7

* Extra long insert barbs

Stainless Steel Male Adapters - For coiled plastic pipe to submersible pump

Order No.	UPC Bar Code (Qty. 1)	MIP Insert Size x Size	Length Inches	Ctn. Qty.	Approx. Wt./Lbs.
WSSMA100 (Hex)	6 42367 08373 1	1" x 1"	3.25"	1	0.4
WSSMA1025 (Hex)	6 42367 08374 8	1-1/4" x 1"	3.25"	1	0.4
WSSMA125 (Hex)	6 42367 08375 5	1-1/4" x 1-1/4"	3.25"	1	0.5
* WSSMA100XL (Hex)	6 42367 10331 6	1" x 1"	4.5"	1	0.4
* WSSMA1025XL (Hex)	6 42367 10333 0	1-1/4" x 1"	4.5"	1	0.5
* WSSMA125XL (Hex)	6 42367 10332 3	1-1/4" x 1-1/4"	4.5"	1	0.5

* Extra long insert barbs

MIP = Male Iron Pipe

FIP = Female Iron Pipe

SLIP = PVC Pipe Slip Glued Connection



CONTACT INFO: Main/International:(712) 732-7354
 U.S. and Iowa:(877) 888-7059
 Fax:(712) 732-7568
 Fax:(800) 269-3569