

w w w . w e l l p r o . c o m

PUMP ACCESSORIES

TORQUE ARRESTORS, SUBMERSIBLE PUMP GUIDES AND
CABLE GUARDS, CABLE TIES, SAFETY ROPES

**We
Pro**



LEAD

*The Water Well
Products
used by
PROFESSIONALS*

**We
Pro**

"The Best Selection, Quality, and Price"



PUMP ACCESSORIES



WSTA48C




WSPG601



WCG46



***WCG100**



WCT66505



WSSR500T

Deluxe Torque Arrestor

- Installed directly above submersible pump. Protects pump from starting torque damage.
 - Clamps 1" or 1-1/4" drop pipe and adjusts to fit 4" thru 8" well casing.
 - Two piece construction.
 - FDA approved compounds in material.
- * Same size torque as STA48C - imported material.

Order No.	UPC Bar Code (Qty.1)	Description	Length	Bag Qty.	Approx. Wt./Lbs.
WSTA48C	6 42367 08342 7	All Stainless Steel	11-3/4"	1	1.5
Clamps Included					
*WSTA48CI	6 42367 11392 6	All Stainless Steel	11-3/4"	1	1.5
Clamps Included					
WSTA48	6 42367 08343 4	Torque Arrestor Only	11-3/4"	1	1.3
No Clamps					

Submersible Pump Guide

Order No.	UPC Bar Code (Qty.1)	Fits Casing I.D.	Outside Dia.	Drop Pipe Size	Approx. Wt./Lbs.
WSPG501	6 42367 10444 3	5-3/16" to 5-5/8"	4-3/4"	1"	0.6
WSPG601	6 42367 10445 0	6"	5-3/4"	1"	0.9

Submersible Cable Guard

- Keeps submersible wire from scraping against well casing, wire can be snapped into holder from outside or strung through openings.
 - Finished in 6" size, tabs may be cut for 4" and 5" casing and can be used on 1" or 1-1/4" drop pipe.
- *WCG100 used for 1" pipe size only. Wrap around design.

Order No.	UPC Bar Code (Qty.1)	Casing I.D.	Bag Qty.	Approx. Wt./Lbs.
WCG46	6 42367 08344 1	4" - 6"	2	0.1
*WCG100	6 42367 10446 7	4" - 6"	2	0.1

Cable Ties

- For tying, bundling applications.

Order No.	UPC Bar Code (Qty.1)	Pipe Size	Length	Pcs./Pkg.	Approx. Lbs./Pkg.
WCT66505	6 42367 08345 8	1/4" - 1-1/4"	8"	100	0.3
WCT66507	6 42367 08346 5	1/4" - 3"	14-1/2"	100	0.4

Safety Rope

- Rope on plastic spool.
- Safety - yellow color, 1/4" polypropylene rope exceeds 1000 lb. test.

Order No.	UPC Bar Code (Qty.1)	Rope Type	Size	Footage On Spool	Approx. Lbs./Spool
WSSR500T	6 42367 08347 2	Twisted	1/4"	600'	9.4
WSSR1200T	6 42367 08348 9	Twisted	1/4"	1200'	16.9
WSSR38600T	6 42367 10447 4	Twisted	3/8"	600'	17.0
WSSR381200T	6 42367 11003 1	Twisted	3/8"	1200'	32.0
WSSR500B	6 42367 08349 6	Braided	1/4"	500'	5.0
WSSR1000B	6 42367 08350 2	Braided	1/4"	1000'	9.5
WSSR3000B	6 42367 08351 9	Braided	1/4"	3000'	30.5
WSSR516500B	6 42367 08352 6	Braided	5/16"	500'	9.0



	CONTACT INFO: Main/International:(712) 732-7354 U.S. and Iowa:(877) 888-7059 Fax:(712) 732-7568 Fax:(800) 269-3569
	Copyright © 2006 WELL PRO
	FORM 5025.1 ISSUED 10/06